

## 7/8" CELLFLEX® Premium Attenuation Low-Loss Foam-Dielectric Coaxial Cable

**Product Description**

CELLFLEX®7/8" premium attenuation low loss flexible cable

Application: Main feed line



7/8" CELLFLEX® Low-Loss Foam Dielectric Coaxial Cable

**Features/Benefits****• Ultra Low Attenuation**

The further reduced attenuation of CELLFLEX® premium attenuation coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.

**• Complete Shielding**

The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.

**• Low VSWR**

Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.

**• Outstanding Intermodulation Performance**

CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.

**• High Power Rating**

Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.

**• Wide Range of Application**

Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

**Technical Features****Structure**

Inner conductor:	Copper Tube	[mm (in)]	9.3 (0.37)
Dielectric:	Foam Polyethylene	[mm (in)]	21.5 (0.85)
Outer conductor:	Corrugated Copper	[mm (in)]	25.2 (0.99)
Jacket:	Polyethylene, PE	[mm (in)]	27.8 (1.09)

**Mechanical Properties**

Weight, approximately	[kg/m (lb/ft)]	0.43 (0.29)
Minimum bending radius, single bending	[mm (in)]	120 (5)
Minimum bending radius, repeated bending	[mm (in)]	250 (10)
Bending moment	[Nm (lb-ft)]	13.0 (9.6)
Max. tensile force	[N (lb)]	1440 (324)
Recommended / maximum clamp spacing	[m (ft)]	0.8 / 1.0 (2.75 / 3.25)

**Electrical Properties**

Characteristic impedance	[Ω]	50 +/- 1
Relative propagation velocity	[%]	90
Capacitance	[pF/m (pF/ft)]	74.0 (22.5)
Inductance	[μH/m (μH/ft)]	0.185 (0.056)
Max. operating frequency	[GHz]	5
Jacket spark test RMS	[V]	8000
Peak power rating	[kW]	85
RF Peak voltage rating	[V]	2920
DC-resistance inner conductor	[Ω/km (Ω/1000ft)]	1.62 (0.494)
DC-resistance outer conductor	[Ω/km (Ω/1000ft)]	1.34 (0.408)

**Recommended Temperature Range**

Storage temperature	[°C (°F)]	-70 to +85 (-94 to +185)
Installation temperature	[°C (°F)]	-40 to +60 (-40 to +140)
Operation temperature	[°C (°F)]	-50 to +85 (-58 to +185)

**Other Characteristics**

Fire Performance:	Halogene Free
VSWR Performance:	Standard [dB (VSWR)] 18 (1.288:1)
Other Options:	Phase stabilized and phase matched cables and assemblies are available upon request.

Frequency [MHz]	Attenuation [dB/100m] [dB/100ft]	Power [kW]
0.5	0.0780	0.0238
1.0	0.110	0.0336
1.5	0.135	0.0412
2.0	0.156	0.0476
10	0.351	0.107
20	0.498	0.152
30	0.612	0.186
50	0.793	0.242
88	1.06	0.323
100	1.13	0.345
108	1.18	0.358
150	1.39	0.425
174	1.50	0.458
200	1.62	0.493
300	2.0	0.608
400	2.32	0.707
450	2.47	0.753
500	2.61	0.796
512	2.64	0.806
600	2.88	0.876
700	3.12	0.951
750	3.24	0.987
800	3.35	1.02
824	3.41	1.04
894	3.56	1.08
900	3.57	1.09
925	3.62	1.10
960	3.70	1.13
1000	3.78	1.15
1250	4.27	1.30
1400	4.54	1.38
1500	4.71	1.44
1700	5.05	1.54
1800	5.21	1.59
2000	5.52	1.68
2100	5.67	1.73
2200	5.82	1.77
2400	6.11	1.86
2500	6.25	1.91
2600	6.39	1.95
2700	6.53	1.99
3000	6.93	2.11
3500	7.56	2.30
4000	8.16	2.49
4900	9.17	2.80
5000	9.28	2.83

Attenuation at 20°C (68°F) cable temperature  
Mean power rating at 40°C (104°F) ambient temperature